



FLAVOR PAPER

sales@flavorpaper.com | flavorpaper.com

CAMOUFLAGE

by Andy Warhol® x Flavor Paper



Warhol's series of Camouflages are imprinted with his primary philosophy: survival depends on seeing without being seen. Long a fascination of Flavor Paper, camo is a beautiful way to present pattern without pattern and Andy managed to make a simple yet flowing camouflage. You can customize your Camo to create a truly unique environment; just don't ask for woodlands! This camouflage is meant to reveal instead of conceal. Let's face it: you were likely to be discovered in front of all of those Day-Glo colors anyway.

©/®/TM The Andy Warhol Foundation for the Visual Arts, Inc.

SPECS

ROLL SIZE ————— 27" W x 180" L
PATTERN REPEAT ————— 27" / 68.58cm
SIDE TO SIDE MATCH ——— STAIRCASE
MANUFACTURED IN USA

LEARN MORE!





FLAVOR PAPER

sales@flavorpaper.com | flavorpaper.com

CAMOUFLAGE

by Andy Warhol® x Flavor Paper



APRICOT

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CHAMPAGNE MYLAR
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



JORDANS

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED THUNDER GRAY
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



MOSSY FIELD

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CHROME MYLAR
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



POPPY FIELD

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I COPPER MYLAR
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED