



FLAVOR PAPER

sales@flavorpaper.com | flavorpaper.com

CHINATOWN TOILE

by Dan Funderburgh



The Chinatown Soccer Club is a crew of artists, photographers, designers, writers, skateboarders and all-around good people that meets year-round for friendly soccer matches. Dan Funderburgh is one of those artists and one can only hope that his fancy footwork is on par with his superb pattern making skills. Specifically designed for the 2008 European Cup in collaboration with Adidas, this classic toile design is filled with depictions of modern life in New York City's Chinatown. The original soft red on matte white scores, but we can print this in any combination you want.

SPECS

ROLL SIZE ————— 27" W x 180" L

PATTERN REPEAT ————— 27" / 68.58cm

SIDE TO SIDE MATCH ——— HALF DROP

MADE TO ORDER IN USA

LEARN MORE!





FLAVOR PAPER

sales@flavorpaper.com | flavorpaper.com

CHINATOWN TOILE

by Dan Funderburgh



LICORICE

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED THUNDER
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



LIGHT SAGE

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I SILVER MYLAR
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



ROUGE

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I MATTE GOLD MYLAR
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



SOFT RED

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED IVORY
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED