



FLAVOR PAPER

sales@flavorpaper.com | flavorpaper.com

# CITY PARK

by Dan Funderburgh



This contemporary classic draws from historic damask pattern style, but twists it decidedly modern with urban content like rats and parking meters. Curators at the Smithsonian were so taken with City Park that they chose it for the Cooper-Hewitt National Design Museum permanent collection. We have the original screen and also the inverse screen, so you can now choose to print the elements or print the background. We can also print this Flavor without rats – a.k.a. uninfested. One fantastic pattern with many ways to make it your own!

## SPECS

ROLL SIZE ————— 27" W x 180" L  
PATTERN REPEAT ————— 19.88" / 50.5cm  
SIDE TO SIDE MATCH ——— STRAIGHT ACROSS  
MADE TO ORDER IN USA

LEARN MORE!







FLAVOR PAPER

sales@flavorpaper.com | flavorpaper.com

CITY PARK

by Dan Funderburgh



## LIGHT BLUE

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED MICA
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



## JADE INVERSE

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED BLUSH
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



## SAMBA

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I MATTE GOLD MYLAR
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



## LIGHT SAGE

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED PLATINUM
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED