



FLAVOR PAPER

sales@flavorpaper.com | flavorpaper.com

HOUSEPLANTED

by Dan Funderburgh



If your interiors need to turn over a new leaf, then Houseplanted is a natural selection. Handmade and homegrown, this pattern portrays the flora Dan Funderburgh – illustrator, artist and frequent Flavor Paper partner – surrounded himself with while living a life indoors for the past few years (sound familiar?), as well as studied and sketched during a Brooklyn garden residency. But, unlike vital varieties that require constant TLC, this cool, cultivated and uncomplicated Flavor field is designed to serve up self-sustaining style and reinvigorating vibes wherever it's seeded...season after season.

SPECS

ROLL SIZE ————— 27" W x 180" L
PATTERN REPEAT ————— 50.49" /128.24cm
SIDE TO SIDE MATCH ——— HALF DROP
MADE TO ORDER IN USA

LEARN MORE!





FLAVOR PAPER

sales@flavorpaper.com | flavorpaper.com

HOUSEPLANTED

by Dan Funderburgh



AFTERGLOW

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED PLATINUM
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



CACTUS

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED BLUSH
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



FLAMINGO

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED LINEN
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



LICORICE

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED IVORY
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED