



FLAVOR PAPER

sales@flavorpaper.com | flavorpaper.com

SHOES

by Andy Warhol® x Flavor Paper



A common theme throughout Andy Warhol's career, shoes were at a new, disco high a la Studio 54 when he resurrected them in 1980. The added flourish of Diamond Dust (actually crushed glass) mimicked the glamour of the Manhattan glitterati he was out with. Flavor Paper took the original Polaroids Warhol used for his paintings and worked the arrangements into a repeating pattern. A modern version of Diamond Dust is available and adds a brilliant touch with a chrome background, which we think Andy would be quite proud of.

©/®/TM The Andy Warhol Foundation for the Visual Arts, Inc.

SPECS

ROLL SIZE ————— 27" W x 180" L
PATTERN REPEAT ————— 56.88" /144.48cm
SIDE TO SIDE MATCH — TWO-THIRDS (2/3) DROP
MADE TO ORDER IN USA

LEARN MORE!





FLAVOR PAPER

sales@flavorpaper.com | flavorpaper.com

SHOES

by Andy Warhol® x Flavor Paper



BLUE SUEDE

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I GOLD PONYSKIN FOIL
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



CHAMPAGNE SPARKLE

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CHAMPAGNE MYLAR
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



GEMSTONE

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CHROME MYLAR
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED



SILVER DIAMOND DUST

- PRINTING METHOD: HANDSCREEN
- GROUND: TYPE I CLAY COATED EBONY
- BACKING: NONWOVEN FIBER
- WEIGHT: 0.78 oz/sqft
- FIRE RATING: CLASS A, AS PER ASTM E 84 (ADHERED)
- FLAME SPREAD/SMOKE DEVELOPED: 15/205
- ECO: PRINTED WITH WATER BASED INKS (LATEX OR ECO-SOLVENT)
- INSTALLATION: COMES UNTRIMMED | PRO INSTALL RECOMMENDED